

# HyperXpress series PCIe Voice Recording Boards



The OptiLogix HyperXpress OEM Voice Recording boards provide powerful features for building advanced Call Recorders.

Each card occupies a single PCI Express slot and combines a compact form factor with very low power consumption resulting in unmatched reliability.

On-board DSPs and large streaming buffers impose very little demand on system and application resources.

D-channel signalling supports Call Setup, Connect, Clear, DDI number and CLI number decoding.

Supports all major ISDN variants, Q.SIG, DASS-2 and DPNSS.

Simultaneous recording on all channels of both upstream and downstream sides of a conversation or optionally recording the audio streams separately (stereo).



## Features and Benefits

High density half length and standard or low profile PCI Express cards

Non intrusive and undetectable high impedance passive monitoring

Dialled number and Caller ID signalling support

Models available for PRI-ISDN, BRI-ISDN / S<sub>0</sub> bus, Digital handsets and Analog handset / trunk lines

Digital Signal Processors for voice streaming and on-board D-channel protocol processing

4, 8 and 16 channel Analog, Digital handset and S<sub>0</sub> bus models

Fractional, 30 and 60 channel PRI-ISDN / E1 models

23 channel and 46 channel T1-ISDN models

Protocol support for all major ISDN variants, Q.SIG, DASS-2 and DPNSS

Analog models support DTMF, FSK Caller ID, AGC and audio detection

Digital models support all major PBX with highly accurate DigitalVox start/stop triggering

Uses the OptiLogix generic API and driver. Fully supported by HyperEngine

Supports Server 2003, Server 2008, Server 2012, Windows 7, Windows 8 and Windows 10

Supports 64kbit/s A-law and high quality compressed 36kbit/s speech encoding

CE, FCC and RoHS2 compliance

## Technical Specifications

|                             |  |
|-----------------------------|--|
| Mechanical characteristics: | Half-length standard or low-profile PCI Express card |
| Operating temperature:      | 0 °C to +60°C  |
| Humidity:                   | 5% to 80% non-condensing                             |
| Maximum power requirements: | +3,3Vdc (300 mA), +12Vdc (150 mA)                    |
| Operating systems:          | All 32-bit and 64-bit Windows Operating Systems      |
| Boards per system:          | Mix of 12 boards or 720 ports total                  |

## Interface Specifications

|                                   |  |
|-----------------------------------|--|
| Primary Rate interface:           | E1 (2.048Mbit/s), T1 (1.544Mbit/s)   |
| AC impedance:                     | 1100 Ω   |
| Maximum tap length:               | 10 m (unterminated), 100 m (terminated)  |
| Protocols:                        | All major ISDN variants, Q.SIG, DASS-2 and DPNSS   |
| Basic Rate interface:             | 4 wire S <sub>0</sub> bus  |
| AC impedance:                     | Line Matched   |
| Maximum tap length:               | 500 m  |
| Protocols:                        | Euro-ISDN  |
| Digital handset interface:        | 2 wire bus   |
| AC impedance:                     | Line Matched   |
| Maximum tap length:               | 500 m  |
| Protocols:                        | All major PBX supported (DigitalVox triggering)  |
| Analog handset / trunk interface: | 2 wire voltage start or line level audio triggering (Vox)  |
| DC/AC impedance:                  | Infinite / 3000 Ω  |
| Maximum tap length:               | 5000 m   |
| Signalling:                       | Ring detection, voltage detection, DTMF detection for dialled numbers, FSK Caller ID detection, voice activity detection |

## Audio Processing

|                                     |   |
|-------------------------------------|---|
| Voice and Silence detection:        | Programmable from OptiLogix API                       |
| Upstream and downstream audio gain: | Programmable from OptiLogix API                       |
| Frequency response:                 | 300-3400Hz (all compression modes)                    |
| Speech encoding/compression:        | 64kbit/s A-law (G.711), 36kbit/s proprietary encoding |

## Safety and EMI Certifications

|                              |                              |
|------------------------------|------------------------------|
| Safety, emissions, immunity: | EN 60950, EN 55022, EN 55024 |
| Compliance:                  | CE, FCC and RoHS2            |
| Estimated MTBF:              | 600.000 hours                |
| Warranty:                    | 3 years                      |

The OptiLogix policy is one of continuous development and consequently the equipment may vary in detail from the description and specification in this publication